

REQUEST FOR BID
SOUTH SALT LAKE CITY

Notice is hereby given that SOUTH SALT LAKE CITY CORPORATION (City) is accepting bids for (3) NEW 15cy (Hook-lift) Roll-off Containers.

Minimum Specifications: Roll-off container must be compatible with a Stellar SLIDer 2OS hook system.

1. 144"L x 48"H x 87"W (inside measurements).
2. Sides: 10-gauge. 50,000 psi minimum yield steel. Floor: 3/16" or 7-gauge
 - a. Floor and Sides must be continuously welded on interior surfaces suitable for dumping. Skip welded on the exterior surfaces.
3. Rails: 6" x 2" x 3/16" tube (minimum), all closed tubing – nothing left open.
4. Top Cap: 3" x 4" x 3/16" tube (all closed tubing – nothing left open).
5. Cross Members: 3" x 4.1" x 3/16" channel 16" on centers.
6. Vertical Wall Stringers: 3" x 4" x 10-gauge (minimum) To run from top cap to floor of container, 20" on centers.
7. Wheels: 10" x 8" steel wheels in rear. Stands on front-end.
8. Door: Frame to be 3" x 4" x 3/16" tube. Door panel to be 10-gauge 50,000 psi minimum yield steel. One piece non-water tight flush rear door.
9. Door Hardware: Door latch to be two-position slam latch style. Single right-hand opening (270 degrees). No header beam above door. All hinges must have grease zerks.
10. Loading Hook: A-Frame hook-lift height at 53" (2" round hook)
11. Paint: All welds must be de-slagged, de-greased and cleaned before painting. All exterior seams are to be sealed before painting. Container to be primed with (2) coats of rust inhibitive primer, inside and outside. Finished with two (2) coats of acrylic DOT white on the exterior.
12. Warranty: One year on complete unit.
13. Delivery: Must be delivered 60 days after bid is awarded. A late fee of 1.5% per day, per unit will be assessed for delivery after promised delivery date.

Bid Instructions:

1. List any variation to each of the listed specifications.
2. List warranty information.
3. List promised delivery time-frame.

Bid Evaluation Process:

Bids will be evaluated by using a points system (0-3 points). Each item below minimum specifications or not offered by vendor's bid will receive 0 points unless satisfactory negotiations are made prior to bid due date.

Important Evaluation Factors:

12X48 RECTANGLE ROLL OFF
 A-FRAME HOOK UP (SPECIAL)
 3" CHANNEL X-MEMBERS- 16" CTC
 3/16" OR 7 GA. FLOOR 10 GA. BODY
 3X4X3/16 TOP TUBES & DOOR FRAME
 3X4X3/16 TUBE SIDE VERTICAL POST - 20" CTC
 10X8" W GROUND ROLLERS REAR, STANDS FRONT
 NO DOOR HEADER
 TARP HOOKS ON ALL STRINGERS

