

- C. **CONSTRUCTION:** No Monument/Marker, or any part thereof, may be constructed of wood, or any other material which is not approved by the Cemetery Sextant.
- D. **PLACEMENT:** Monuments/Markers must be placed at the Head End of the Burial Plot. No other structure or marker is allowed.
- E. **INSTALLATION:** Installation of the Monument/Marker shall be performed by a Monument/Marker company. All Monuments/Markers shall be placed in accordance with the instructions and conditions of the Cemetery Sextant, and only after payment of the Monument/Marker locating fee. Attaching ropes or cables to trees or other objects in the Cemetery, and placing material on adjoining Plots or allowing the same to remain on the ground longer than is necessary, is prohibited. The Cemetery Sextant may require that planks or plywood be placed over grass or paths any time a vehicle is driven on it.
- F. **MONUMENT/MARKER REQUIREMENTS**

1. **Concrete Border:** A four (4) inch wide concrete border is required around all Monuments/Markers, including those that are flat.
2. **Vertical Monument Foundations:** Each Monument shall be placed on a concrete foundation which will be a minimum thickness of eight (8) inches; the top of the foundation shall be set 4" above ground level; the base of the Monument shall be a minimum of (4) four inches from the edge of the concrete foundation.
3. **Monument/Marker Dimensions:** The maximum Monument/Marker size the City shall allow is eighty (80) percent of a single Plot width, excluding concrete border; and two (2) feet in depth, including concrete border. A single Monument/Marker may be placed on two adjacent Plots under the same ownership; however, the Monument/Marker may not exceed sixty (60) percent of the combined width. No Monument/Marker may exceed sixty (60) inches in height.

