

1 **CHAPTER 13.74: FLOOD DAMAGE PREVENTION REGULATIONS**

2
3 **SECTION:**

4 Article I. Overview

5 13.74.005: Statutory Authorization

6 **13.74.010: Findings**

7 13.74.020: Purpose Of Provisions

8 13.74.030: Methods Of Reducing Flood Losses

9 Article II. Definitions

10 13.74.040: Definitions Of Words And Phrases

11 Article III. General Provisions

12 13.74.051: Lands To Which This Chapter Applies

13 **13.74.052: Basis For Establishing The Areas Of Special Flood Hazard**

14 13.74.053: Establishment Of Development Permit

15 13.74.054: Compliance

16 13.74.055: Abrogation And Greater Restrictions

17 13.74.056: Interpretation

18 13.74.057: Warning And Disclaimer Of Liability

19 Article IV. Administration

20 13.74.060: Designation Of The Floodplain Administrator

21 13.74.061: Duties And Responsibilities Of The Floodplain Administrator

22 13.74.062: Permit Procedures

23 13.74.063: Variance Procedures

24 Article V. Provisions For Flood Hazard Reduction

25 13.74.070: Special Flood Hazard Areas Permit Procedures

26 13.74.071: Specific Standards

27 13.74.072: Standards For Subdivision Proposals

28 13.74.073: Standards For Areas Of Shallow Flooding

29 13.74.074: Floodways

30 13.74.080: Adoption Of Floodplain Regulations Required

31 13.74.081: Penalties For Noncompliance

32
33 **ARTICLE I. OVERVIEW**

34 13.74.005: STATUTORY AUTHORIZATION:

35 The legislature of the state of Utah has delegated the responsibility to local governmental units to adopt regulations designed
36 to minimize flood losses. (Ord. 2012-15, 9-20-2012)

37
38 13.74.010: FINDINGS:

39 A. The flood hazard areas of Holladay are subject to periodic inundation which results in loss of life and property, health
40 and safety hazards, disruption of commerce and governmental services, and extraordinary public expenditures for flood
41 protection and relief, all of which adversely affect the public health, safety and general welfare.

42 B. These flood losses are created by the cumulative effect of obstructions in floodplains which cause an increase in flood
43 heights and velocities, and by the occupancy of flood hazard areas by uses vulnerable to floods and hazardous to other lands
44 because they are inadequately elevated, floodproofed or otherwise protected from flood damage.

45 **C. The city of Holladay hereby adopts the FEMA flood insurance rate maps (FIRM) and effective FEMA flood insurance**
46 **studies (FIS) and all subsequent maps and studies of FEMA. (Ord. 2012-15, 9-20-2012)**

47
48 13.74.020: PURPOSE OF PROVISIONS:

49 It is the purpose of this chapter to promote the public health, safety and general welfare and to minimize public and private
50 losses due to flood conditions in specific areas by provisions designed to:

51 A. Protect human life and health;

Draft Amendment Planning Commission 09/07/2021

- 52 B. Minimize expenditure of public money for costly flood control projects;
- 53 C. Minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the
- 54 general public;
- 55 D. Minimize prolonged business interruptions;
- 56 E. Minimize damage to public facilities and utilities such as water and gas mains, electric, telephone and sewer lines,
- 57 streets and bridges located in floodplains;
- 58 F. Help maintain a stable tax base by providing for the sound use and development of flood prone areas in such a manner
- 59 as to minimize future flood blight areas; and
- 60 G. Ensure that potential buyers are notified that property is in a flood area. (Ord. 2012-15, 9-20-2012)

61

62 13.74.030: METHODS OF REDUCING FLOOD LOSSES:

- 63 A. In order to accomplish its purposes, this chapter uses the following methods:
- 64 1. Restrict or prohibit uses that are dangerous to health, safety or property in times of flood, or cause excessive increases
- 65 in flood heights or velocities;
- 66 2. Require that uses vulnerable to floods, including facilities which serve such uses, be protected against flood damage
- 67 at the time of initial construction;
- 68 3. Control the alteration of natural floodplains, stream channels, and natural protective barriers, which are involved in
- 69 the accommodation of floodwaters;
- 70 4. Control filling, grading, dredging and other development which may increase flood damage;
- 71 5. Prevent or regulate the construction of flood barriers which will unnaturally divert floodwaters or which may increase
- 72 flood hazards to other lands. (Ord. 2012-15, 9-20-2012)

73

74 **ARTICLE II. DEFINITIONS**

75 13.74.040: DEFINITIONS OF WORDS AND PHRASES:

76 See section 13.04.040 of this title. (Ord. 2012-15, 9-20-2012)

77

78 **ARTICLE III. GENERAL PROVISIONS**

79 13.74.051: LANDS TO WHICH THIS CHAPTER APPLIES:

80 This chapter shall apply to all areas of special flood hazard within the jurisdiction of the city of Holladay. (Ord. 2012-15, 9-

81 20-2012)

82

83 **13.74.052: BASIS FOR ESTABLISHING THE AREAS OF SPECIAL FLOOD HAZARD:**

84 The areas of special flood hazard identified by the federal emergency management agency in a scientific and engineering

85 report entitled, "The Flood Insurance Study For City Of Holladay", dated ~~September 25, 2009~~ November 19, 2021, with

86 accompanying flood insurance rate maps and flood boundary-floodway maps (FIRMs and FBFMs) and any revisions thereto

87 are hereby adopted by reference and declared to be a part of this chapter. (Ord. 2012-15, 9-20-2012)

88

89 13.74.053: ESTABLISHMENT OF DEVELOPMENT PERMIT:

90 A development permit shall be required to ensure conformance with the provisions of this chapter. (Ord. 2012-15, 9-20-2012)

91

92 13.74.054: COMPLIANCE:

93 No structure or land shall hereafter be located, altered, or have its use changed without full compliance with the terms of this

94 chapter and other applicable regulations. (Ord. 2012-15, 9-20-2012)

95

96 13.74.055: ABROGATION AND GREATER RESTRICTIONS:

97 This chapter is not intended to repeal, abrogate, or impair any existing easements, covenants, or deed restrictions. However,

98 where this chapter and another ordinance, easement, covenant, or deed restriction conflict or overlap, whichever imposes the

99 more stringent restrictions shall prevail. (Ord. 2012-15, 9-20-2012)

100

101 13.74.056: INTERPRETATION:

Draft Amendment Planning Commission 09/07/2021

In the interpretation and application of this chapter, all provisions shall be:

- A. Considered as minimum requirements;
- B. Liberally construed in favor of the governing body; and
- C. Deemed neither to limit nor repeal any other powers granted under state statutes. (Ord. 2012-15, 9-20-2012)

13.74.057: WARNING AND DISCLAIMER OF LIABILITY:

The degree of flood protection required by this chapter is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. On rare occasions greater floods can and will occur and flood heights may be increased by manmade or natural causes. This chapter does not imply that land outside the areas of special flood hazards or uses permitted within such areas will be free from flooding or flood damages. This chapter shall not create liability on the part of the community or any official or employee thereof for any flood damages that result from reliance on this chapter or any administrative decision lawfully made thereunder. (Ord. 2012-15, 9-20-2012)

ARTICLE IV. ADMINISTRATION

13.74.060: DESIGNATION OF THE FLOODPLAIN ADMINISTRATOR:

The community development director is hereby appointed the floodplain administrator to administer and implement the provisions of this chapter and other appropriate sections of 44 CFR (national flood insurance program regulations) pertaining to floodplain management. (Ord. 2012-15, 9-20-2012)

13.74.061: DUTIES AND RESPONSIBILITIES OF THE FLOODPLAIN ADMINISTRATOR:

Duties and responsibilities of the floodplain administrator or designee shall include, but not be limited to, the following:

- A. Maintain and hold open for public inspection all records pertaining to the provisions of this chapter.
- B. Review permit applications to determine whether a proposed building site, including the placement of manufactured homes, will be reasonably safe from flooding.
- C. Review, approve or deny all applications for development permits required by adoption of this chapter.
- D. Review permits for proposed development to assure that all necessary permits have been obtained from those federal, state or local governmental agencies (including section 404 of the federal water pollution control act amendments of 1972, 33 USC 1334) from which prior approval is required.
- E. Where interpretation is needed as to the exact location of the boundaries of the areas of special flood hazards (for example, where there appears to be a conflict between a mapped boundary and actual field conditions) the floodplain administrator shall make the necessary interpretation.
- F. Notify, in riverine situations, adjacent communities and the state coordinating agency prior to any alteration or relocation of a watercourse, and submit evidence of such notification to the federal emergency management agency.
- G. Assure that the flood carrying capacity within the altered or relocated portion of any watercourse is maintained.
- H. When base flood elevation data has not been provided in accordance with section 13.74.052 of this chapter, the floodplain administrator shall obtain, review and reasonably utilize any base flood elevation data and floodway data available from a federal, state or other source, in order to administer the provisions of article V of this chapter.
- I. When a regulatory floodway has not been designated, the floodplain administrator must require that no new construction, substantial improvements, or other development (including fill) shall be permitted within zones A1-30 and AE on the community's FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot (1') at any point within the community.
- J. Under the provisions of 44 CFR chapter 1, section 65.12, of the national flood insurance program regulations, a community may approve certain development in zones A1-30, AE, AH, on the community's FIRM which increases the water surface elevation of the base flood by more than one foot (1'), provided that the community first applies for a conditional FIRM revision through FEMA (conditional letter of map revision). (Ord. 2012-15, 9-20-2012)

13.74.062: PERMIT PROCEDURES:

Application for a development permit shall be presented to the floodplain administrator on forms furnished by him/her and may include, but not be limited to, plans in duplicate drawn to scale showing the location, dimensions, and elevation of

proposed landscape alterations, existing and proposed structures, including the placement of manufactured homes, and the location of the foregoing in relation to areas of special flood hazard. Additionally, the following information is required:

A. Elevation (in relation to mean sea level), of the lowest floor (including basement) of all new and substantially improved structures;

B. Elevation in relation to mean sea level to which any nonresidential structure shall be floodproofed;

C. A certificate from a registered professional engineer or architect that the nonresidential floodproofed structure shall meet the floodproofing criteria of subsection 13.74.071B of this chapter;

D. Description of the extent to which any watercourse or natural drainage will be altered or relocated as a result of proposed development;

E. Maintain a record of all such information in accordance with subsection 13.74.061A of this article;

Approval or denial of a development permit by the floodplain administrator shall be based on all of the provisions of this chapter and the following relevant factors:

A. The danger to life and property due to flooding or erosion damage;

B. The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner;

C. The danger that materials may be swept onto other lands to the injury of others;

D. The compatibility of the proposed use with existing and anticipated development;

E. The safety of access to the property in times of flood for ordinary and emergency vehicles;

F. The costs of providing governmental services during and after flood conditions including maintenance and repair of streets and bridges, and public utilities and facilities such as sewer, gas, electrical and water systems;

G. The expected heights, velocity, duration, rate of rise and sediment transport of the floodwaters and the effects of wave action, if applicable, expected at the site;

H. The necessity to the facility of a waterfront location, where applicable;

I. The availability of alternative locations, not subject to flooding or erosion damage, for the proposed use;

J. The relationship of the proposed use to the comprehensive plan for that area. (Ord. 2012-15, 9-20-2012)

13.74.063: VARIANCE PROCEDURES:

A. The appeal board as established by the community shall hear and render judgment on requests for variances from the requirements of this chapter.

B. The appeal board shall hear and render judgment on an appeal only when it is alleged there is an error in any requirement, decision, or determination made by the floodplain administrator in the enforcement or administration of this chapter.

C. Any person or persons aggrieved by the decision of the appeal board may appeal such decision in the courts of competent jurisdiction.

D. The floodplain administrator shall maintain a record of all actions involving an appeal and shall report variances to the federal emergency management agency upon request.

E. Variances may be issued for the reconstruction, rehabilitation or restoration of structures listed on the national register of historic places or the state inventory of historic places, without regard to the procedures set forth in the remainder of this chapter.

F. Variances may be issued for new construction and substantial improvements to be erected on a lot of one-half (1/2) acre or less in size contiguous to and surrounded by lots with existing structures constructed below the base flood level, providing the relevant factors in section 13.74.062 of this chapter have been fully considered. As the lot size increases beyond the one-half (1/2) acre, the technical justification required for issuing the variance increases.

G. Upon consideration of the factors noted above and the intent of this chapter, the appeal board may attach such conditions to the granting of variances as it deems necessary to further the purpose and objectives of this chapter (section 13.74.020 of this chapter).

H. Variances shall not be issued within any designated floodway if any increase in flood levels during the base flood discharge would result.

I. Variances may be issued for the repair or rehabilitation of historic structures upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and the variance is the minimum necessary to preserve the historic character and design of the structure.

- J. Prerequisites for granting variances:
1. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
 2. Variances shall only be issued upon:
 - a. Showing a good and sufficient cause;
 - b. A determination that failure to grant the variance would result in exceptional hardship to the applicant; and
 - c. A determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisances, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
 3. Any applicant to whom a variance is granted shall be given written notice that the structure will be permitted to be built with the lowest floor elevation below the base flood elevation, and that the cost of flood insurance will be commensurate with the increased risk resulting from the reduced lowest floor elevation.
- K. Variances may be issued by a community for new construction and substantial improvements and for other development necessary for the conduct of a functionally dependent use provided that:
1. The criteria outlined in subsections A through I of this section are met, and
 2. The structure or other development is protected by methods that minimize flood damages during the base flood and create no additional threats to public safety. (Ord. 2012-15, 9-20-2012)

ARTICLE V. PROVISIONS FOR FLOOD HAZARD REDUCTION

13.74.070: SPECIAL FLOOD HAZARD AREAS PERMIT PROCEDURES:

In all areas of special flood hazards the following provisions are required for all new construction and substantial improvements:

- A. All new construction or substantial improvements shall be designed (or modified) and adequately anchored to prevent flotation, collapse or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy;
- B. All new construction or substantial improvements shall be constructed by methods and practices that minimize flood damage;
- C. All new construction or substantial improvements shall be constructed with materials resistant to flood damage;
- D. All new construction or substantial improvements shall be constructed with electrical, heating, ventilation, plumbing, and air conditioning equipment and other service facilities that are designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding;
- E. All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of floodwaters into the system;
- F. New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of floodwaters into the system and discharge from the systems into floodwaters; and
- G. On site waste disposal systems shall be located to avoid impairment to them or contamination from them during flooding. (Ord. 2012-15, 9-20-2012)

13.74.071: SPECIFIC STANDARDS:

In all areas of special flood hazards where base flood elevation data has been provided as set forth in: a) section 13.74.052 of this chapter, b) subsection 13.74.061H of this chapter, or c) subsection 13.74.072C of this chapter, the following provisions are required:

- A. Residential Construction: New construction and substantial improvement of any residential structure shall have the lowest floor (including basement), elevated to or above the base flood elevation. A registered professional engineer, architect, or land surveyor shall submit a certification to the floodplain administrator that the standard of this subsection as proposed in this chapter, is satisfied.
- B. Nonresidential Construction: New construction and substantial improvements of any commercial, industrial or other nonresidential structure shall either have the lowest floor (including basement) elevated to or above the base flood level or together with attendant utility and sanitary facilities, be designed so that below the base flood level the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy. A registered professional engineer or architect shall

254 develop and/or review structural design, specifications, and plans for the construction, and shall certify that the design and
255 methods of construction are in accordance with accepted standards of practice as outlined in this subsection. A record of such
256 certification which includes the specific elevation (in relation to mean sea level) to which such structures are floodproofed
257 shall be maintained by the floodplain administrator.

258 C. Enclosures: New construction and substantial improvements, with fully enclosed areas below the lowest floor that are
259 usable solely for parking of vehicles, building access or storage in an area other than a basement and which are subject to
260 flooding shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and
261 exit of floodwaters. Designs for meeting this requirement must either be certified by a registered professional engineer or
262 architect or meet or exceed the following minimum criteria:

263 1. A minimum of two (2) openings having a total net area of not less than one square inch for every square foot of
264 enclosed area subject to flooding shall be provided.

265 2. The bottom of all openings shall be no higher than one foot (1') above grade.

266 3. Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the
267 automatic entry and exit of floodwaters.

268 D. Manufactured Homes:

269 1. Require that all manufactured homes to be placed within zone A on a community's FHBM or FIRM shall be installed
270 using methods and practices which minimize flood damage. For the purposes of this requirement, manufactured homes must
271 be elevated and anchored to resist flotation, collapse, or lateral movement. Methods of anchoring may include, but are not
272 limited to, use of over the top or frame ties to ground anchors. This requirement is in addition to applicable state and local
273 anchoring requirements for resisting wind forces.

274 2. Require that manufactured homes that are placed or substantially improved within zones A1-30, AH, and AE on the
275 community's FIRM on sites: a) outside of a manufactured home park or subdivision, b) in a new manufactured home park or
276 subdivision, c) in an expansion to an existing manufactured home park or subdivision, or d) in an existing manufactured
277 home park or subdivision on which a manufactured home has incurred "substantial damage" as a result of a flood, be elevated
278 on a permanent foundation such that the lowest floor of the manufactured home is elevated to or above the base flood
279 elevation and be securely anchored to an adequately anchored foundation system to resist flotation, collapse, and lateral
280 movement.

281 3. Require that manufactured homes be placed or substantially improved on sites in an existing manufactured home park
282 or subdivision within zones A1-30, AH and AE on the community's FIRM that are not subject to the provisions of this
283 section be elevated so that either:

284 a. The lowest floor of the manufactured home is at or above the base flood elevation, or

285 b. The manufactured home chassis is supported by reinforced piers or other foundation elements of at least equivalent
286 strength that are no less than thirty six inches (36") in height above grade and be securely anchored to an adequately anchored
287 foundation system to resist flotation, collapse, and lateral movement.

288 E. Recreational Vehicles: Require that recreational vehicles placed on sites within zones A1-30, AH, and AE on the
289 community's FIRM either:

290 1. Be on the site for fewer than one hundred eighty (180) consecutive days,

291 2. Be fully licensed and ready for highway use, or

292 3. Meet the permit requirements of section 13.74.062 of this chapter, and the elevation and anchoring requirements for
293 "manufactured homes" in this section. A recreational vehicle is ready for highway use if it is on its wheels or jacking system,
294 is attached to the site only by quick disconnect type utilities and security devices, and has no permanently attached additions.

296 13.74.072: STANDARDS FOR SUBDIVISION PROPOSALS:

297 A. All subdivision proposals including the placement of manufactured home parks and subdivisions shall be consistent
298 with sections 13.74.010, 13.74.020 and 13.74.030 of this chapter.

299 B. All proposals for the development of subdivisions including the placement of manufactured home parks and
300 subdivisions shall meet development permit requirements of sections 13.74.053 and 13.74.062 of this chapter, and the
301 provisions of this article.

302 C. Base flood elevation data shall be generated for subdivision proposals and other proposed development including the
303 placement of manufactured home parks and subdivisions which is greater than fifty (50) lots or five (5) acres, whichever is
304 less, if not otherwise provided pursuant to section 13.74.052 or subsection 13.74.061H of this chapter.

D. All subdivision proposals including the placement of manufactured home parks and subdivisions shall have adequate drainage provided to reduce exposure to flood hazards.

E. All subdivision proposals including the placement of manufactured home parks and subdivisions shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize or eliminate flood damage. (Ord. 2012-15, 9-20-2012)

13.74.073: STANDARDS FOR AREAS OF SHALLOW FLOODING:

Located within the areas of special flood hazard established in section 13.74.052 of this chapter, are areas designated as shallow flooding. These areas have special flood hazards associated with base flood depths of one to three feet (3') where a clearly defined channel does not exist and where the path of flooding is unpredictable and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow; therefore, the following provisions apply:

A. All new construction and substantial improvements of residential structures have the lowest floor (including basement) elevated above the highest abutting grade at least as high as the depth number specified in feet on the community's FIRM (at least 2 feet if no depth number is specified). (Ord. 2015-02, 2-5-2015)

B. All new construction and substantial improvements of nonresidential structures:

1. Have the lowest floor (including basement) elevated above the highest adjacent grade at least as high as the depth number specified in feet on the community's FIRM (at least 2 feet if no depth number is specified); or

2. Together with attendant utility and sanitary facilities be designed so that below the base flood level the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads of effects of buoyancy.

C. A registered professional engineer or architect shall submit a certification to the floodplain administrator that the standards of this section, as proposed in section 13.74.062 of this chapter, are satisfied.

D. Require within zones AH or AO adequate drainage paths around structures on slopes, to guide floodwaters around and away from proposed structures. (Ord. 2012-15, 9-20-2012)

13.74.074: FLOODWAYS:

Located within areas of special flood hazard established in section 13.74.052 of this chapter, are areas designated as floodways. Since the floodway is an extremely hazardous area due to the velocity of floodwaters which carry debris, potential projectiles and erosion potential, the following provisions shall apply:

A. Encroachments are prohibited, including fill, new construction, substantial improvements and other development within the adopted regulatory floodway unless it has been demonstrated through hydrologic and hydraulic analyses performed in accordance with standard engineering practice that the proposed encroachment would not result in any increase in flood levels within the community during the occurrence of the base flood discharge.

B. If subsection A of this section is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of this article.

C. Under the provisions of 44 CFR chapter 1, section 65.12, of the national flood insurance regulations, a community may permit encroachments within the adopted regulatory floodway that would result in an increase in base flood elevations, provided that the community first applies for a conditional FIRM and floodway revision through FEMA. (Ord. 2012-15, 9-20-2012)

13.74.080: ADOPTION OF FLOODPLAIN REGULATIONS REQUIRED:

In accordance with section 59.2(b) of CFR 44, chapter 1, of the national flood insurance program (NFIP) regulation, to qualify for the sale of federally subsidized flood insurance, a community must adopt floodplain management regulations that meet or exceed the minimum standards of section 60. "These regulations must include effective enforcement provisions". In accordance with section 60.1(b) of CFR 44, chapter 1, of the NFIP regulations, "These regulations must be legally enforceable, applied uniformly throughout the community to all privately and publicly owned land within flood prone (i.e., mudflow) or flood related erosion areas, and the community must provide that the regulations take precedence over less restrictive conflicting local laws, ordinances or codes". (Ord. 2012-15, 9-20-2012)

13.74.081: PENALTIES FOR NONCOMPLIANCE:

No structure or land shall hereafter be constructed, located, extended, converted, or altered without full compliance with the terms of this chapter and other applicable regulations. Violation of the provisions of this chapter by failure to comply with

357 any of its requirements (including violations of conditions and safeguards established in connection with conditions) shall
358 constitute a misdemeanor. Any person who violates this chapter or fails to comply with any of its requirements shall upon
359 conviction thereof be fined not more than ten thousand dollars (\$10,000.00) or imprisoned for not more than thirty (30) days,
360 or both, for each violation, and in addition shall pay all costs and expenses involved in the case. Nothing herein contained
361 shall prevent the city of Holladay from taking such other lawful action as is necessary to prevent or remedy any violation.
362 (Ord. 2012-15, 9-20-2012)